


COUNTERTOP Point-of-Sale



T2

Big Solutions in a Small Package

Featuring a compact design, the T2 offers all the latest features, including EMV and NFC, and provides high efficiency while taking up minimal counter space. Designed with the user-experience in mind, the backlit keypad, large keys and color display touchscreen make it easy to use while reducing instances of PIN entry errors.




- **SECURE**
Meets the highest industry security requirements
- **FUTURE-PROOF**
EMV & NFC capability that keep you relevant and compliant with today's payment solutions
- **EXPANDABLE**
Multiple connectivity options, from Ethernet and Dial with optional WiFi

CERTIFICATIONS



www.exadigm.com



Features & Benefits

Robust Compliance - Built-in security transaction engine offers merchants the highest level of secure payment processing.

NFC Support - Improves customer experience by offering support for mobile wallet applications. Certified for both PayPass and PayWave.

EMV Support - Reinforces your confidence that transactions are secure.

E-Signature - Allows you to minimize fraud risk and reduce paper output.

Premium User Experience - A color display touchscreen makes viewing transactions easier than ever before.

Terminal Access Portal (TAP)

ExaDigm's Terminal Access Portal (TAP) provides the fastest, most secure and truly cost-effective remote device management tool for a wide range of users. Featuring a user-friendly interface, TAP can be accessed anytime, anywhere, ensuring real-time device management.

Specifications

Processor	ARM Cortex-A9, 32-bit secure processor
Memory	256 MB Flash, 128 MB SDRAM
Slots	3 PSAM card slots 1 SD card slot
Card Readers	Contactless - ISO/IEC 14443 Magstripe - 3 track, bi-directional Smart card - ISO 7816
Display	2.8 inch color capacitive screen, 240 x 320
Keypad	10 operational keys, 10 functional keys
Audio	Buzzer
Thermal Printer	Paper roll W x D = 58mm x 45mm
Ports	1 USB host 1 Micro USB 1 RS232 1 PIN pad 1 LAN 1 PSTN
PIN Pad	Internal or External (G101), 3DES encryption, DUKPT key management
Communication	Ethernet and Dial, WiFi (optional)
Size	L x W x H = 175 x 81 x 72mm
Weight	320g
Environment	Operating temperature: 0°C to 50°C (32°F to 122°F); storage temperature: -20°C to 60°C (-4°F to 140°F); humidity (non-condense): 5% to 95%
Power Supply	Input: 100-240V, 50-60Hz Output: 8.5V/2.5A
Certifications	PCI PTS 4.0, PA-DSS 3.x, Paywave, Paypass, EMV Level 1 & 2